

Volkswagen Amarok

Theoretical ground clearance (unladen weight) depending on SEIKEL lift kit and tyre size

Tyre size	Standard ground clearance in mm	Tyre size		Installation SEIKEL ● lift kit	Theoretical ground clearance Middle of front axle		Necessary kit / conversion			Possible treads	
		Standard size	Larger than standard		in mm	Extra height	Speedo test	Speedo adjustment	Steering stop limit	A/T	M/T
Standard tyres	WITHOUT drive train protection				More ground clearance in mm than standard						
205/80 R16	230	●		●	255	+ 25					
245/70 R16	230	●		●	255	+ 25				●	
245/65 R17	230	●		●	255	+ 25					
245/70 R17	230	●		●	255	+ 25				●	●
255/60 R18	230	●		●	255	+ 25					
255/55 R19	230	●		●	255	+ 25					
Conversion sizes											
225/75 R16	230	identical		without	230	+/- 0				●	
225/75 R16	230	identical		●	255	+ 25					
245/75 R16			●	●	265	+ 35	●		●	●	●
245/75 R17			●	●	280	+ 50		●	●	●	
265/70 R17			●	●	280	+ 50		●	●	●	●
265/65 R18			●	●	280	+ 50		●	●	●	
255/55 R20			●	●	265	+ 35		●	●	●	

Information not guaranteed, subject to error and change without notice.

SEIKEL GmbH - 02/2017